

PATENT
Docket No.: FR000003
Customer No. 000024737

Amendment to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

*S-10
b1*

1. (currently amended) An image processing method for providing three-dimensional geometric modeling of the spine, using a biplanar image reconstruction, comprising: steps of acquisition of
 acquiring a first view (F) of a part of the spine; and
 acquiring a second view (L) of the same part of the spine taken from a different angle around the longitudinal axis of the spine;
 matching the dimensions of the views (F,L) from two predetermined corresponding landmarks (P1, P2) on each view;
 performing a spline calculation for providing a smoothed axial line (FAC, LAC) on each view, the spline calculation including mathematical modeling of drawn piece-wise linear curves on a respective one of the first and second views, previously set by a control means of a drawing program, for supplying respective new digital smoothed curves, the new digital smoothed curves being constructed with interpolated values provided between points of the respective piece-wise linear curves, the new digital smoothed curves corresponding to a respective smoothed axial line (FAC, LAC) on each view; and
 deriving three-dimensional coordinates (z, x, y) of corresponding points (P) along the spine as a function of the smoothed axial lines (FAC, LAC).

A-2

2. (currently amended) An The image processing method as claimed in Claim 1, wherein, for matching the two views, an axial line (FAL, LAL) is drawn on the spine on

PATENT
Docket No.: FR000003
Customer No. 000024737

each view, and the two landmarks (P1, P2) are set on said axial line on each view.

3. (currently amended) An The image processing method as claimed in claim 2, wherein the matching of the dimensions of the two views is performed by a calculating matching coordinates $[(x_{F1}, z_{F1}), (y_{L1}, z_{L1}); (x_{F2}, z_{F2}), (y_{L2}, z_{L2})]$ for the two corresponding landmarks (P1, P2).

4. (currently amended) An The image processing method as claimed in Claim 3, wherein a common system of coordinates (Z, X, Y) is determined for the two views, from the matched coordinates of the two corresponding landmarks.

5. (cancelled)

6. (currently amended) An The image processing method as claimed in ~~one of claims 2 to 5~~ Claim 2, wherein three-dimensional coordinates (z, x, y) of corresponding points along the spine are determined for points (P) regularly spaced along the axis of coordinates (Z) corresponding to the longitudinal axis of the spine.

7. (currently amended) An The image processing method as claimed in ~~one of claims 2 to 6~~ Claim 2, wherein the common system of coordinates is an orthogonal system, the first view is a frontal view (F), the second view is a lateral view (L) orthogonal to the frontal view, with a common axis (Z) in the direction of the longitudinal axis of the spine, a second axis (X) parallel to the frontal plane of view and the third axis (Y) parallel to the lateral plane of view.

8. (currently amended) An imaging system having acquisition means for acquiring a first and a second view of the spine, having display means to display the two views of the spine, having drawing means to draw axial lines of the spine and to set

PATENT
Docket No.: FR000003
Customer No. 000024737

predetermined corresponding landmarks on each view and having processing means to calculate three-dimensional coordinates of points along the spine according to the method as claimed in ~~one of claims 1 to 7~~ Claim 1.

9. (currently amended) An ~~The~~ imaging system as claimed in Claim 8, wherein the processing means comprise a suitably programmed computer of at least one selected from the group consisting of a workstation ~~or~~ and a special purpose processor having circuit means, which are arranged to process image data according to the method as claimed in ~~any of Claims 1 to 7~~ Claim 1, and wherein the display means display images processed according to said method, further comprising means to store the image data.

10. (currently amended) An X-ray examination apparatus having a system as claimed in ~~one of Claims 8 or 9~~ Claim 8.

11. (currently amended) A computer program product comprising a set of instructions for carrying out the method as claimed in ~~one of Claims 1 to 7~~ Claim 1.